

ProAc RESPONSE TWO POINT FIVE



Outstanding power and clarity from a completely new design.

This brand new floorstanding model from ProAc delivers music on a scale and with a potency normally experienced only with loudspeakers twice this size. For the audiophile restricted by considerations of space or funds, the Two Point Fives offer a credible and sophisticated large-scale performance.

Slim and elegant, the cabinets are constructed with walls of varying thickness and are all heavily damped, rendering them almost inert and therefore free of colouration.

Each houses an astonishing new power-house bass/midrange driver, never before used in a ProAc design. This seven-inch carbon fibre unit has a special patented surround and unique magnet system. When loaded through a high back pressure equalised reflex port, this driver develops unbelievable bass extension and transient control. The $\frac{3}{4}$ " soft dome tweeter is already an established ProAc favourite, used

 **ProAc**
perfectly natural



in several current models. Its smooth and silky output combines with the bass/midrange unit to produce a completely natural and involving musical experience.

As might be expected, all the standard ProAc virtues are exhibited by the Two Point Fives. Exceptional detail, pinpoint imagery and almost three-dimensional soundstaging are all portrayed with stunning clarity. What will not be expected though, is the sheer scale, power and authority generated from cabinets of this size.

The full potential of these thoroughbred designs will only be realised through the use of the highest quality partnering equipment.

SPECIFICATION

Nominal Impedance:	8 ohms
Recommended Amplifiers:	20 to 200 watts
Frequency Response:	20hz to 30Khz
Sensitivity:	86db linear for 1 watt at 1 metre
Bass/Midrange Driver:	ProAc 7" (178mm) carbon fibre unit in die-cast chassis, with special surround and magnet system.
Tweeter:	ProAc ¾" (19mm) soft dome with honeycomb - wound voice coil. Special damping and ferrofluid-cooled assembly.
Crossover:	Highest quality components with pure oxygen-free multi-strand copper wiring. Split for optional bi-wiring and bi-amping.
Dimensions:	42" (1066mm) high on plinths with spikes. 8¾" (222mm) wide 10" (254mm) deep
Weight:	53lbs (24kg)/cabinet
Mode:	Floorstanding on dedicated plinths.
Grille:	Acoustically transparent crimplene
Finish:	Available in the following real wood veneers: Black Ash, Walnut, Natural Oak, Mahogany, Cherry, Rosewood, Yew, Ebony, Bird's Eye Maple, Burr Oak.

* Due to our policy of continuous improvement all specifications are subject to change without notice. Cabinets pictured are finished in burr oak real wood veneer. Since wood is a natural product, both colour and grain patterns may vary.