

ProAc RESPONSE THREE



New standards of imagery in monitor loudspeaker design.

The new RESPONSE range of loudspeakers from ProAc will redefine the state-of-the-art in loudspeaker design. The culmination of twenty years design experience, they incorporate the very finest components and materials available. Exhaustively researched and tested using the latest technology, the RESPONSE range allows the full realisation of the potential of high quality ancillary equipment.

A floorstanding monitor, the RESPONSE THREE is the tallest and most innovative speaker designed to date by ProAc. Slim and elegant, this model breaks new ground in terms of sound presentation. Through the painstaking development of the M.I.O.P. (mirror image offset placement) drive unit layout, a deep, wide soundstage and quality of imagery has been produced which has to be experienced to be believed. The overall effect is of the speakers virtually disappearing from the scene.

 **ProAc**
perfectly natural



The drive units themselves are the finest available. Of special interest is the tweeter, a new model which produces unrivalled neutrality and detail - more so, we believe, than even electrostatic or ribbon-type tweeters. Critically positioned between two specially designed Scanspeak bass/midrange drivers this tweeter establishes a new reference standard for high-frequency performance. The bass/midrange drivers are modified to ProAc specifications and provide a tight, fast and extended bass whilst combining with the tweeter to generate an exceptionally open and detailed midrange.

Cabinet construction is impressive even by ProAc standards, using one-inch thick M.D.F. throughout. All internal surface are damped with anechoic grade foam. The crossover utilises only the fine components and is split for optional bi-amping.

Optimum stability and coupling ensured through a special one-inch thick plinth which is bolted to the base of the cabinet. Floor spikes are in turn screwed into the plinth.

The RESPONSE THREE fuses the very latest technology to inspired design - the result is an uncannily involving and compelling musical experience.

SPECIFICATION

Nominal Impedance:	8 ohms
Recommended Amplifiers:	20 to 250 watts
Frequency Response:	20hz to 25Khz
Sensitivity:	88db linear for 1 watt at 1 metre
Bass/Midrange Driver:	ProAc 6½" (165mm) polypropylene unit in die-cast chassis with special damping, designed in conjunction with Scanspeak of Denmark. Special voice coil, pole piece, dustcap and magnet assembly.
Tweeter:	1" (25mm) dome with special coating and unique rear loading. Ferrofluid-cooled coil assembly.
Crossover:	Highest quality components. A refined version of the design used in the Response One and Two models.
Dimensions:	47" (1194mm) high (on plinth). 11" (279mm) wide 12" (304mm) deep
Mode:	Floorstanding on special plinths.
Grille:	Acoustically transparent.
Finish:	Teak, Walnut and Black Ash as standard. Others to order.

* Due to our policy of continuous improvement all specifications are subject to change without notice.