

# ProAc TABLETTE 50 SIGNATURE



## **The ultimate mini-monitor design.**

The Tablette 50 Signature is the zenith of the Tablette formula, establishing a new reference level in mini-monitor performance. The original ProAc Tablette was launched in 1979 and was quickly acclaimed as a breakthrough in miniature loudspeaker design. As new drive units and ancillary materials have become available the basic model has been re-vamped several times, culminating in the most recent incarnation, the widely-acclaimed Tablette 50.

This Signature model blends an inspired design with the very latest refinements in drive unit technology to deliver natural and detailed reproduction set in an astonishingly large soundstage. The Signature remains faithful to the music, emphasising nothing yet revealing all.

Virtually all aspects of the basic Tablette 50 design have been enhanced and refined in the Signature. Bass has been tightened and become even more controlled through the introduction of a sophisticated new five inch bass/midrange driver.

 **ProAc**  
*perfectly natural*



This unit features a special copper magnet assembly, copper phase plug and polycarbon cone, set in a die-cast chassis. Loaded by twin open reflex ports in the rear of the cabinet, bass response is powerful and extended yet remains crisp and clearly defined.

A superb new 3/4" dome tweeter, as used in our prestigious Response models, delivers incredible detail and openness whilst retaining a distinctive sweetness and fluency. Mated seamlessly by a specially dedicated crossover network, the drive units are housed in a formidable cabinet, critically strengthened and heavily damped to cope with the high power levels which the drivers generate.

Although the Tablette 50 Signature can be shelf-mounted, high mass stands with good rigidity are preferable for optimum results. The full potential of these thoroughbred designs will only be realised through the use of the highest quality partnering equipment.

## SPECIFICATION

<b>Nominal Impedance:</b>	8 ohms
<b>Recommended Amplifiers:</b>	20 to 150 watts
<b>Frequency Response:</b>	35hz to 30Khz
<b>Sensitivity:</b>	87db linear for 1 watt at 1 metre
<b>Bass/Midrange Driver:</b>	Special 5" (127mm) polycarbon unit with copper magnet assembly, die-cast chassis, copper phase plug.
<b>Tweeter:</b>	Special 3/4" (19mm) soft dome with honeycomb wound voice coil and ferrofluid cooling.
<b>Crossover:</b>	Finest components on dedicated circuit board. Multistrand oxygen-free copper throughout. Split for optional bi-wiring and bi-amping.
<b>Dimensions:</b>	11" (279mm) high (on plinth). 6½" (165mm) wide 9" (229mm) deep
<b>Weight:</b>	13lbs (6kg)/cabinet
<b>Mode:</b>	Stand/Shelf mounting.
<b>Grille:</b>	Acoustically transparent crimplene.
<b>Finish:</b>	Available in the following real wood veneers: Ebony, Burr Oak, Birds Eye Maple.

\* Due to our policy of continuous improvement all specifications are subject to change without notice.