

ProAc **RESPONSE D25**



To improve on the highly acclaimed Response 2.5 would have been a daunting task but for the development of a new generation of highly efficient and sensitive drive units. The faultless reproduction throughout the frequency range which made the 2.5 such a world-beater has not only been sustained but greatly intensified in the new D25. Good quality valve or Class A transistor amplifiers with an output as low as 10 watts will produce fine results from these exciting new loudspeakers.

The original cabinet dimensions have been retained, but there the similarity ends. The cabinets themselves, handcrafted and finished in real wood veneers, are extremely rigid and heavily damped as before, but the introduction of a large flared port beneath the plinths gives better interaction with the listening room, making cabinet placement less critical.

ProAc **RESPONSE D25**

New vitality and
potency from an
internationally
acclaimed design

 **ProAc**
perfectly natural



ProAc RESPONSE D25

An entirely new 6½" bass/midrange driver, built by one of the UK's leading studio monitor manufacturers, is used in tandem with a radical new one inch soft dome tweeter. This combination is harmonised through a sophisticated HQC crossover network and ProAc oxygen-free wiring, delivering exceptional power handling, efficiency and sensitivity.

The D25 is like a breath of fresh air, with an immediacy and dynamism which reaches out to touch the listener. The improved sensitivity squeezes every detail out of any type of recording and the classic ProAc virtues of low colouration, fine balance and sweet smoothness ensure an unforgettable listening experience at a very reasonable price level.



Specification

Nominal Impedance	8 ohms
Recommended Amplifiers	10 to 200 watts
Frequency Response	20hz to 30Khz
Sensitivity	88db linear for 1 watt at 1 metre
Bass/Midrange Driver	6½" (165mm) ProAc unit with coated polypropylene cone on die-cast chassis
Tweeter	ProAc 1" (25mm) soft dome with special surround and inner damping
Crossover	HQC crossover using dedicated components wired throughout with multi-strand oxygen-free cable. Split for optional bi-wiring and bi-amping.
Dimensions	42" (1066mm) high on plinths with conical feet 8¾" (222mm) wide 10" (254mm) deep
Weight	57 lbs (26kg) /cabinet
Mode	Floorstanding
Grille	Acoustically transparent crimplene
Finish	Available in the following real wood veneers: Black Ash, Maple, Mahogany, Cherry, Yew, Ebony, Bird's Eye Maple and other finishes to special order

* Due to our policy of continuous improvement all specifications are subject to change without notice. Cabinets pictured are finished in Ebony real wood veneer. Since wood is a natural product, both colour and grain patterns may vary.