

# RESPONSE SATELLITE

High end satellites.

## Specification

<b>Nominal Impedance</b>	8 ohms
<b>Recommended Amplifiers</b>	10 to 100 watts (150 watts + filtered)
<b>Frequency Response</b>	80 Hz to 30 kHz
<b>Sensitivity</b>	86 dB linear for 1 watt at 1 metre
<b>Bass/Midrange Driver</b>	4½" ProAc chassis, specially developed cone and dust cap.
<b>Tweeter</b>	1" (25 mm) soft silk dome with neodymium magnet and radial fin cooling.
<b>Crossover</b>	Finest components on dedicated circuit board. Multistrand oxygenfree cable throughout. Split for optional bi-wiring and bi-amping.
<b>Dimensions</b>	8½" (216 mm) high 5½" (140 mm) wide 6" (152 mm) deep with grille
<b>Weight</b>	8 lb (3.6 kg)
<b>Mode</b>	Stand/Shelf/Wall mounting
<b>Grille</b>	Acoustically transparent crimplene
<b>Finish</b>	Available in the following real wood veneers: Black Ash, Mahogany, Cherry and Maple.



Shown in Cherry wood veneer

# RESPONSE CENTRE

High end satellite centre.

## Specification

<b>Nominal Impedance</b>	8 ohms	<b>Crossover</b>	Finest components on dedicated circuit board. Multistrand oxygenfree cable throughout. Split for optional bi-wiring and bi-amping.
<b>Recommended Amplifiers</b>	10 to 200 watts (250 watts + filtered)	<b>Dimensions</b>	5½" (140 mm) high 13" (330 mm) wide 6" (152 mm) deep with grille
<b>Frequency Response</b>	80 Hz to 30 kHz	<b>Weight</b>	12 lb (5.6 kg)
<b>Sensitivity</b>	86 dB linear for 1 watt at 1 metre	<b>Mode</b>	Stand/Shelf/Wall mounting
<b>Bass/Midrange Driver</b>	Drivers (2) 4½" ProAc chassis, specially developed cone and dust cap.	<b>Grille</b>	Acoustically transparent crimplene
<b>Tweeter</b>	1" (25 mm) soft silk dome with neodymium magnet and radial fin cooling.	<b>Finish</b>	Available in the following real wood veneers: Black Ash, Mahogany, Cherry and Maple.



Shown in Cherry wood veneer

